

PIKO Table

STP1



The picture is only illustrative, it may not exactly match the product described.

Product description	Steel weldment. The construction consists of two sides, welded from sheet metal burn parts, which carry 6 wooden boards of rectangular shape (117×42 mm) with a length of 1780 mm fixed by stainless steel screws to the supporting structure.
Material	Construction: steel grade 11 Solid wood: spruce, oak, wood pine ThermoWood® DOWNLOAD PDF SAMPLER >
Surface treatment	Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty). Other RAL shades according to RAL sampler on request only. Spruce – two-layer impregnation and lacquer mixed with water with beeswax Oak – treated with impregnation and a glaze with biocidal effect Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection
Dimensions	1800×712×720 mm / 54 kg
Anchoring	Anchoring is done with four stainless steel threaded rods M10 of length min. 100 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance. A detailed drawing is available for download on the website for each particular product.

